

2019 Stock Truck Rules

General

- Half ton, 3/4 ton and 1 ton allowed
- **MUST** have a helmet and eye protection
- **Must** have functioning seatbelts (lap belt only is permitted but we will check to be sure it fastens)
- Long pants and shirt required, sturdy shoes required
- Any Engine Allowed
- Any Driveshaft allowed
- No Braced rear ends or aftermarket axles
- No Braced Transmissions
- 4wd must remove an axle

Vehicle Preperation

- **MUST** Remove all exterior lighting, trim, plastic moldings, chrome, antennas, hub caps, mirrors, ANYTHING that may break or fall off during competition
- Trailer hitches **MUST** be removed
- **MUST** Remove all interior carpeting, headliner, rear seats, plastic trim, all glass **MUST** be removed, dash **MAY** stay in or be removed
- Headers **are** permitted
- **MUST** have a roof sign
- Stock gas tank **MUST** be removed.
- Max 12 gallon steel tank to be placed in back seat area securely fastened (no ratchet straps) or off of rear seat bar (details under cage section)
- Fuel lines **must** be run through the firewall with steel tubing or thick rubber hose minimum where the line passes through the firewall. BE SMART WITH HOSE CLAMPS
- Electric Fuel pump **MUST** have a clearly marked ON/OFF switch
- Up to 2 Automotive batteries may be used and are to be located in the passenger front floor area and **must** be well secured
- Hood **MUST** have a minimum of 12"x12" hole for fire access
- **Must** have 2 steel straps, rods or chains running from roof to windshield opening area for drivers protection. This is NOT to add any reinforcement.
- **MAY** use aftermarket shifters and pedals.
- Driver's door **MUST** be painted bright yellow or orange
- Radiator **must** remain in stock location or be removed (no radibarrels)
- **ANY PLY** tires allowed up to 33" tall, doubled or tubed is allowed, AIR ONLY

Hood

- HOOD MUST BE OPEN FOR INSPECTION!!!!
- May have up to 6 hold downs TOTAL. Front 2 MAY be threaded rod 1" max diameter. The other 4 MUST be wire (3 passes max), Chain (2 passes Max), Angle iron bolted together (no longer than 3" on angle) or seatbelts passing through sheet metal only
- Threaded rod must be vertical (no bends) and May go to frame

Bed

- May have 4 extra body bolts 1" max 6x6 washers
- Box sides must remain vertical, don't pound them over
- Tailgate must remain upright and in stock location
- Tailgate may be secured in 4 places total, chain, wire or weld 5x3 strap

Doors

- Driver's door MAY be welded solid
- Other doors may be welded 5" on and 5" off with 3" wide plates MAX
- May also use chains or #9 wire in 2 places per door seam (nothing to frame) 2 passes per chain, 3 passes per #9 wire location

Bumpers

- ANY automotive bumper may be used aside from Chrysler V bumpers
- Bumpers MAY NOT be stuffed or loaded
- Bumpers may be mounted by bolting or welding
- In place of an automotive bumper you may use a single piece of steel tubing (straight only no homemade points) up to 2x6x 1/4" thick, no wider than the front of the vehicle (tire to tire) (4x4x1/4 is legal) ends must be open
- You are allowed 6" per side steel tube inside or plate outside of Frame to mount bumper
- Front 2 threaded rod may pass through tubing or plate
- Front frame MAY be cut back no farther than factory core support location prior to mounting bumper
- ALLOWED AND HIGHLY RECOMMENDED 2 lengths of chain or #9 wire running from bumper to upper core support only. This is to hold the bumper in the event it comes loose, not to strengthen the car. 1 pass chain, 2 pass #9 wire, don't get creative here
- Rear bumper must be stock or same tube as above

Body and Frame

- Aside from patch rule DO NOT weld frame for any reason other than is listed as allowed.
- DO NOT weld body to frame in any way
- Body creasing is not allowed
- PATCH RULE, you will be allowed up to four 4x4x1/4" plates per VEHICLE, NOT PER SIDE. These **MUST** be in an area where a previous bend can be seen clearly!!
- NO Stuffing or filling of frame
- NO extra body bolts and factory bolts may not be altered (accept in bed)
- Fenders **may** be trimmed for clearance and bolted in 6 places max
- May weld bed to cab from the outside of each bedside only

interior protection

- All tubing no larger than 6" diameter
- 4 point cage is permitted consisting of 1 bar behind the seat, a dash bar and 2 door bars connecting them.

Steering and Suspension

- May clamp springs 6 per side 3" wide material max
- stock springs only
- max height 26" to bottom of frame/bumper
- Minimum 20" frame height
- Stock steering components (aftermarket column is okay)

IF IT IS NOT LISTED IN THE RULES DON'T DO IT!

If you need clarification contact us and we will make sure everyone is aware of any clarification